

Product datasheet

Specifications



Acti9 IC2000 outdoor (2 - 2000 lux) twilight switch

CCT15369

Price: 157,909.09 NGN

Main

range of product	Acti9
Product name	Acti9 IC
Product or component type	Twilight switch
Device short name	IC2000
Provided equipment	twilight sensor outdoor
Load type	incandescent lamp: 2600 W halogen lamp: 2600 W non-corrected fluorescent tube: 2300 VA serial-compensated fluorescent tube: 2300 VA parallel compensated fluorescent lamp: 730 VA (80 µF) compact fluorescent lamp: 170 W < 2 W LED lamp: 30 W > 2 W LED lamp: 200 W

Complementary

Device application	Building
Number of channels	1
Maximum power consumption in W	0.5 W stand by
[Ue] rated operational voltage	230 V AC +10 % -15 % at 50/60 Hz
Maximum switching current	10 A - 250 V AC pf = 0.6 16 A - 250 V AC pf = 1
Minimum switching current	10 mA 230 V AC 100 mA 24 V AC/DC
Electrical insulation class	Class II
Output type	Dry contact
Accuracy	+/- 0.25 s/day 25 °C
Contacts type and composition	1 NO
Time delay	20 s on 80 s off
Light intensity adjustment	2...2000 lux
Connections - terminals	1 x 2.5 mm² screw terminals solid or flexible with sleeve 2 x 0.5...2.5 mm² screw terminals solid or flexible
Mounting support	TH35 DIN rail conforming to EN 60715
Height	85.5 mm
Width	18 mm
Depth	67 mm

Disclaimer: This documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications

Net weight	111 g
Overvoltage category	Class 3
Marking	CE
Control type	By brightness detection

Environment

Ambient air temperature for operation	-30...55 °C
ambient air temp for storage/ transportation	-30...70 °C
Relative humidity	90 %, non-condensing
IP degree of protection	IP20 IP55 (sensor)
Standards	EN 60669-2-1

Packing Units

Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Height	6.5 cm
Package 1 Width	8.0 cm
Package 1 Length	10.5 cm
Package 1 Weight	161.0 g
Unit Type of Package 2	S03
Number of Units in Package 2	40
Package 2 Height	30 cm
Package 2 Width	30 cm
Package 2 Length	40 cm
Package 2 Weight	6.89 kg
Package 3 Height	80 cm

Environmental Data

Schneider Electric aims to achieve Net Zero status by 2050 through supply chain partnerships, lower impact materials, and circularity via our ongoing “Use Better, Use Longer, Use Again” campaign to extend product lifetimes and recyclability.

How this information helps you >

Environmental footprint

Environmental Disclosure

[Product Environmental Profile](#)

Use Better

Materials and Substances

Packaging made with recycled cardboard	No
Packaging without single use plastic	No
EU RoHS Directive	Compliant with Exemptions
SCIP Number	7267ef83-877b-4767-8e69-8d32bf47494a
REACH Regulation	REACH Declaration
China RoHS Regulation	China RoHS declaration

Use Again

Repack and remanufacture

Circularity Profile

[End of Life Information](#)

WEEE



The product must be disposed on European Union markets following specific waste collection and never end up in rubbish bins

Take-back

No