

AvatarOn, card switch, 16 A, 250 V, Wood

E8331EKT_WD

Main

Range	AvatarOn
Product or component type	Card switch
Device application	Hotel
Load type	Resistive
Colour tint	Wood

Complementary

-		
Device presentation	Complete product	
Rated current	16 A at 250 V AC 50 Hz	
Connections - terminals	brass terminal	
Clamping connection capacity	3 x 4 mm² for solid cable(s) 3 x 4 mm² for stranded cable(s) 2 x 2.5 mm² for solid cable(s) 2 x 2.5 mm² for stranded cable(s)	
Status LED	LED (amber)	
Material	Polycarbonate: plastic part	
Device mounting	Flush Surface	
Width	86 mm	
Height	86 mm	
Depth	43.8 mm	
Embedding depth	34.1 mm	

Environment

IP degree of protection	IP20
Ambient air temperature for operation	040 °C
Ambient air temperature for storage	060 °C
Ambient air temperature for storage	000 °C
Relative humidity	095 %
Standards	IEC 60669-2-1

Packing Units

Jnit Type of	Package 1	PCE

List Price displayed is VAT EXCLUSIVE.

Number of Units in Package 1	1
Package 1 Height	4.4 cm
Package 1 Width	8.6 cm
Package 1 Length	8.6 cm
Package 1 Weight	124.0 g
Unit Type of Package 2	CAR
Number of Units in Package 2	8
Package 2 Height	9.0 cm
Package 2 Width	19.0 cm
Package 2 Length	19.5 cm
Package 2 Weight	1.042 kg



Schneider Electric aims to achieve Net Zero status by 2050 through supply chain partnerships, lower impact materials, and circularity via our ongoing "Use Better, Use Longer, Use Again" campaign to extend product lifetimes and recyclability.

Environmental Data explained >

How we assess product sustainability >

⊘ Environmental footprint	
Carbon footprint (kg.eq.CO2 per CR, Total Life cycle)	216
Environmental Disclosure	Product Environmental Profile

Use Better

Yes
No
Compliant with Exemptions
REACh Declaration
China RoHS declaration

Use Again

Circularity Profile	End of Life Information
Take-back	No