

Bảng thông số sản phẩm

Thông số kỹ thuật



Long terminal shield for spreaders,
ComPacT NSX400/630, pitch
52.5mm, IP40, 4 poles

LV432596

Main

Product or component type	Long terminal shield
Range compatibility	ComPacT new generation ComPacT NSX400 new generation ComPacT new generation ComPacT NSX630 new generation ComPact ComPact NSX400 ComPact ComPact NSX630 EasyPact EasyPact CVS400 EasyPact EasyPact CVS630 ComPact Compact INV ComPact ComPacT INS
Accessory / separate part type	Insulation accessories
Poles description	4P
Quantity per set	1

Complementary

Connection pitch	52.5 mm
IP degree of protection	IP40 conforming to IEC 60529

Packing Units

Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Height	10.0 cm
Package 1 Width	15.5 cm
Package 1 Length	24.0 cm
Package 1 Weight	458.0 g
Unit Type of Package 2	S04
Number of Units in Package 2	10
Package 2 Height	30.0 cm
Package 2 Width	40.0 cm
Package 2 Length	60.0 cm
Package 2 Weight	5.396 kg

Contractual warranty

Warranty	18 months
----------	-----------

Miễn trừ trách nhiệm: Tài liệu này không nhằm thay thế và không được sử dụng để xác định tính phù hợp hoặc độ tin cậy của các sản phẩm này cho các ứng dụng người dùng cụ thể

Environmental Data

Schneider Electric nhắm đến việc đạt được vị trí Net Zero vào năm 2050 thông qua các quan hệ đối tác chuỗi cung ứng, giảm vật liệu tác động và sự tuần hoàn thông qua chiến dịch "Use Better, Use Longer, Use Again" đang diễn ra của chúng tôi để kéo dài tuổi thọ sản phẩm và khả năng tái chế.

Dữ liệu môi trường đã giải thích >

Cách chúng tôi đánh giá tính bền vững của sản phẩm >

Ảnh hưởng môi trường

Environmental Disclosure

[Product Environmental Profile](#)



Accepted

Use Better

Vật liệu và Bao bì

Packaging made with recycled cardboard

No

Packaging without single use plastic

No

[EU RoHS Directive](#)

Pro-active compliance
(Product out of EU RoHS legal scope)

REACH Regulation

[REACH Declaration](#)

China RoHS Regulation

[China RoHS declaration](#)

Use Again

Đóng gói lại và tái sản xuất

Circularity Profile

No need of specific recycling operations

Halogen content performance	Product contains halogen above thresholds
Take-back	No